



NUOVO - S

KEY FEATURES:



Low Noise



Comfort



Tread Life



Wet Performance

- Silent, smooth, and obstacle-ready design.
- Superb durability and easy handling.
- Durable design, cool under pressure, quick response.
- Exceptional grip in all weather conditions, rain or shine.

NEW!





NUOVO - S

SIZE SPECIFICATION

15"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
185 / 55 R15	86	V	●	585	194	7.4	6.0
185 / 60 R15	88	H	●	603	189	7.4	5.5
195 / 50 R15	82	V		577	201	7.4	6.0
195 / 55 R15	85	V		595	201	7.4	6.0
195 / 60 R15	88	H		615	201	7.4	6.0
195 / 65 R15	91	V		635	201	7.4	6.0

16"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
195 / 50 R16	88	V	●	602	201	7.4	6.0
205 / 50 ZR16	91	W	●	612	214	7.4	6.5
205 / 55 ZR16	94	W	●	632	214	7.4	6.5
215 / 55 ZR16	97	W		642	226	7.4	7.0

17"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
205 / 45 ZR17	84	W		616	206	7.4	7.0
205 / 55 ZR17	95	W	●	658	214	7.4	6.5
215 / 45 ZR17	91	W	●	626	213	7.4	7.0
215 / 50 ZR17	95	W	●	648	226	7.4	7.0
215 / 55 ZR17	98	W	●	668	226	7.4	7.0
225 / 45 ZR17	94	W	●	634	225	7.4	7.5
225 / 50 ZR17	98	W	●	658	233	7.4	7.0
225 / 55 ZR17	101	W	●	680	233	7.4	7.0
235 / 55 ZR17	103	W	●	690	245	7.4	7.5
235 / 45 ZR17	97	W	●	644	236	7.4	8.0
245 / 45 ZR17	99	W	●	652	243	7.4	8.0

18"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
215 / 45 ZR18	93	W	●	651	213	7.4	8.0
215 / 55 ZR18	99	W	●	693	226	7.4	7.0
225 / 40 ZR18	92	W	●	637	230	7.4	7.5
225 / 45 ZR18	95	W	●	659	225	7.4	7.5
225 / 50 ZR18	95	W	●	683	235	7.4	7.5
225 / 55 ZR18	98	V	●	705	233	7.4	7.0
235 / 40 ZR18	95	W	●	645	241	7.4	8.0
235 / 50 ZR18	101	W	●	693	245	7.4	7.5
235 / 55 ZR18	104	W	●	715	245	7.4	7.5
245 / 40 ZR18	97	Y	●	653	248	7.4	7.5
245 / 45 ZR18	100	W	●	677	243	7.4	8.0

19"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
225 / 45 ZR19	96	W	●	647	241	7.4	8.5
235 / 45 ZR19	99	W	●	695	236	7.4	8.0
245 / 35 ZR19	93	W	●	655	248	7.4	8.0
245 / 40 ZR19	98	Y	●	679	248	7.4	8.5
275 / 35 ZR19	100	Y	●	675	278	7.4	9.5

20"

SIZES	LI	SS	XL / RF	INFLATED TYRE DIMENSION			MEASURING RIM(INCH)
				OD(MM)	SW(MM)	NSD(MM)	
285 / 50 R20	116	V	●	794	297	7.8	9.0



STAMFORD TYRES (M) SDN. BHD. (Co. No.:
16, Jalan Jurunilai U1/20, Section U1, Hicom Glenmarie Industrial Park,
40150 Shah Alam, Selangor, Malaysia.
TEL: 603 5569 3094 / 603 5569 3397
Toll Free: 1800 88 0366

STAMFORD Tyres

SOLE DISTRIBUTOR:

